95 mm 2.74 mm XX 50C100X8CSP/TP 50C100X8CSP/TP 50C100X8CSP/TP 50C200X8CSP/TP 50C100X8CSP/TP 50C200X8CSP/TP 50C200X8CSP/TP 50C200X8CSP/TP 50C200X8CSP/TP 50C200X8CSP/TP NOTES: 1 1 MATERIAL: MSTORX BUTTON CAP SCREW, TAMPERPROOF Viewska, specified X:xx +/-0.100 FINISH: PASSIVATE MSTORX BUTTON CAP SCREW, TAMPERPROOF Viewska, specified X:xx +/-0.100 X:xx +/-0.100 FINISH: PASSIVATE .50CXXX8BCSP/TP Beawn BY: LCLARY FSCM No. 6	PART NUMBER .50C20XBCSP/TP .50C40XBCSP/TP .50C50XBCSP/TP .50C60XBCSP/TP			ed dential perty	is drawing and the ormation containe rein are the confid d proprietary prop Global Supply LLC
NOTES: 1. INTERPRET DRAWINGS PER ISD 7380 STANDARD. 2. ROHS AND REACH COMPLIANT. STAINLESS STEEL DRAWING SCALE: MATERIAL: METRIC MATERIAL: Stainless Steel DESCRIPTION: MS stain Stainless Steel PARANCES: INTER PRETION: MATERIAL: Stainless Steel DESCRIPTION: MS STORX BUTTON CAP SCREW, TAMPERPROOF PART NUMBER: Stainless Steel Unless specified X.XXX +/- 0.100 X.XXX +/- 0.100 FINISH: PASSIVATE PART NUMBER: .SOCXXXBCSP/TP	10 X # 21 X	20			1000
SociadoxBCSP/TP SociadoxBCSOCIADOX METRIC		2.74 mm — 🗸	2.7		9.5 mm
SOCI60XBCSP/TP SOC200XBCSP/TP SOC20X					
Image: Solution of the second seco				<u> </u>	
INTERPRET DRAWINGS PER ISO 7380 STANDARD. INTERPRET DRAWINGS PER ISO 7380 STANDARD. ROHES AND REACH COMPLIANT. INTERPRET DRAWINGS PER ISO 7380 STANDARD. ROHES AND REACH COMPLIANT. INTERPRET DRAWINGS PER ISO 7380 STANDARD. INTERPRET DRAWINGS SALE: METRIC MATERIAL: Unless specified X.XXX +/- 0.100 WATERIAL: DESCRIPTION: MS TORX BUTTON CAP SCREW, TAMPERPROOF TOLERANCES: WINSS SALE MATERIAL: DESCRIPTION: MS TORX BUTTON CAP SCREW, TAMPERPROOF TOLERANCES: WINSS SALE METRIC STAINLESS STEEL PART NUMBER: JURIES SALE BRAWN BY: L CLARY FSCM No.		1			1
VOTES: M5 x 0.8 mm Thread L. INTERPRET DRAWINGS PER ISO 7380 STANDARD. E 2. ROHS AND REACH COMPLIANT. E DRAWING SCALE: MATERIAL: METRIC MATERIAL: Stainless Steel M5 torx button cap screw, tamperproof TOLERANCES: x.xx +/- 0.100 Unless specified x.xx +/- 0.100 x.xx +/- 0.100 FINISH: PASSIVATE PART NUMBER: .50CXXXBCSP/TP DRAWN BY: LCLARY FSCM No.		MAMMA			1 000
DRAWING SCALE: MATERIAL: DESCRIPTION: METRIC STAINLESS STEEL MS TORX BUTTON CAP SCREW, TAMPERPROOF TOLERANCES: x.xxx +/- 0.100 FINISH: Unless specified otherwise, all dimensions are in millimeters x.xx +/- 0.100 DRAWN BY: L CLARY		M5 x 0.8 mr		9)	CG
TOLERANCES: Unless specified otherwise, all dimensions are in millimeters X.XXX +/- 0.100 X.XX +/- 0.100 FINISH: PASSIVATE PART NUMBER: .50CXXXBCSP/TP DRAWN BY: L CLARY FSCM No.		ARD.	STANDARD.	GS PER ISO 7380 S	NTERPRET DRAWING
Unless specified otherwise, all dimensions are in millimeters DRAWN BY: L CLARY L CLARY	DESCRIPTION:	ARD. ➡ MATERIAL:	1	GS PER ISO 7380 S OMPLIANT.	NTERPRET DRAWING ROHS AND REACH CC RAWING SCALE:
	DESCRIPTION:	ARD. ➡ MATERIAL:	1	GS PER ISO 7380 S OMPLIANT.	NTERPRET DRAWING ROHS AND REACH CO RAWING SCALE: MET
	DESCRIPTION: SS STEEL M5 TORX BUTTON CAP SCREW, TAMPERPROOF PART NUMBER:	ARD. MATERIAL: STAINLESS STEEL FINISH:	MATERIAL:	GS PER ISO 7380 S OMPLIANT. FRIC x.xxx +/- 0.100 x.xx +/- 0.100	NTERPRET DRAWING ROHS AND REACH CC RAWING SCALE: MET DLERANCES: herwise, all mensions are in
	DESCRIPTION: SS STEEL DESCRIPTION: M5 TORX BUTTON CAP SCREW, TAMPERPROOF PART NUMBER: .50CXXXBCSP/TP	ARD. MATERIAL: STAINLESS STEEL FINISH: PASSIVATE	MATERIAL:	GS PER ISO 7380 S OMPLIANT. FRIC x.xxx +/- 0.100 x.xx +/- 0.100 x.x +/- 0.100	NTERPRET DRAWING ROHS AND REACH CC RAWING SCALE: MET DLERANCES: herwise, all mensions are in illimeters
INITIAL RELEASE LIA Sep 13, 2018	DESCRIPTION: M5 TORX BUTTON CAP SCREW, TAMPERPROOF VATE PART NUMBER: A No.	ARD. MATERIAL: STAINLESS STEEL FINISH: PASSIVATE FSCM No.	FINISH:	GS PER ISO 7380 S OMPLIANT. FRIC x.xxx +/- 0.100 x.xx +/- 0.100 x.x +/- 0.100 RY	NTERPRET DRAWING ROHS AND REACH CC AWING SCALE: MET DIERANCES: herwise, all mensions are in illimeters AWN BY: L CLAI
	DESCRIPTION: M5 TORX BUTTON CAP SCREW, TAMPERPROOF VATE PART NUMBER: A No.	ARD. MATERIAL: STAINLESS STEEL FINISH: PASSIVATE	FINISH:	GS PER ISO 7380 S OMPLIANT. FRIC x.xxx +/- 0.100 x.xx +/- 0.100 x.x +/- 0.100 RY ROVAL DATE	NTERPRET DRAWING ROHS AND REACH CC AWING SCALE: MET DERANCES: herwise, all mensions are in illimeters RAWN BY: L CLAI REV: APPF
ECCN EAR99 = NLR (No License Required) HARDWARE, FASTENERS & COMPON 1el: 408 960 0370 Fax: 408 960 0375 Web: www.globalsuppl	DESCRIPTION: M5 TORX BUTTON CAP SCREW, TAMPERPROOF VATE PART NUMBER: .50CXXXBCSP/TP A No. 012	ARD. MATERIAL: STAINLESS STEEL FINISH: PASSIVATE FSCM No.	FINISH:	GS PER ISO 7380 S OMPLIANT. FRIC x.xxx +/- 0.100 x.xx +/- 0.100 x.x +/- 0.100 RY ROVAL DATE	NTERPRET DRAWING ROHS AND REACH CC AWING SCALE: MET DERANCES: herwise, all mensions are in illimeters RAWN BY: L CLAI REV: APPF