| nformation co | | | | PART NUMBE | R LENGTH |
|---|-------------|-------------------------------------|---------------------------------|---|--------------|
| herein are the | | | | .80C120SFCSP | 12 mm |
| and proprietar | | | | .80C140SFCSP | 14 mm |
| of Global Supp | NY LLC | | | .80C160SFCSP | 16 mm |
| | | | | .80C200SFCSP | 20 mm |
| | | | xx | .80C220SFCSP | 22 mm |
| 12- | 40 | | | .80C250SFCSP | 25 mm |
| - | — 16 mm – | - | | .80C300SFCSP | 30 mm |
| | | | × 1 | .80C350SFCSP | |
| | - | | | .80C400SFCSP | 40 mm |
| / | | | | .80C450SFCSP | 45 mm |
| $\langle \cap \rangle$ | | | / mm | .80C500SFCSP | |
| | | | | .80C550SFCSP | 55 mm |
| (| 0 0 | | 90° | .80C600SFCSP | 60 mm |
| NOTES: INTERPRET DR 2. DIMENSIONS / 3. ROHS AND RE/ | AND TOLERAN | CES PER ISO 73 | 380-1, BN 1593. | | |
| DRAWING SCALE: | | | | DESCRIPTION | |
| METRIC | | | MATERIAL: A2 STAINLESS STEEL | DESCRIPTION: M8 X 1.25 SOCKET HEAD FLAT CAP SCREW | |
| TOLERANCES: | | +/- 0.100 +/- 0.100 +/- 0.100 | FINISH: PASSIVATE | PART NUMBER: .80CXXSFCSP | |
| Unless specified otherwise, all dimensions are in millimeters | | | | | |
| Unless specified otherwise, all dimensions are in | | | FSCM No. | | |
| Unless specified otherwise, all dimensions are in millimeters DRAWN BY: | x.x 4 | DATE: | | | |
| Unless specified otherwise, all dimensions are in millimeters | x.x + | DATE: Oct 31, 2018 | FSCM No. 67012 | Global Sup | ply llc |
| Unless specified otherwise, all dimensions are in millimeters DRAWN BY: REV: | x.x + | | | Global Sup Worldwide Supplier O Hardware, Fasteners & | F ELECTRONIC |
| Unless specified otherwise, all dimensions are in | x.x + | | | | |