information co	ontained				PART NUMBER	LENGTH
herein are the confidential					25C16MCBN	1/4
and proprietary property of Global Supply LLC				25C20MCBN	5/16	
					25C24MCBN	3/8
					25C32MCBN	1/2
					25C40MCBN	5/8
				165	25C48MCBN	3/4
					25C56MCBN	7/8
					25C64MCBN	1
					25C80MCBN	1 1/4
					25C96MCBN	1 1/2
1					25C112MCBN	1 3/4
0.0					25C128MCBN	2
			54-0.075 – N    LAVAVA	NANANANANANANAN	25C160MCBN	2 1/2
NOTES	- 0.498-0.525	-	0.084-0.105			
INTERPRET DE 2. DIMENSIONS	RAWINGS PER / & TOLERANCES	ASME Y14.5M- S PER ANSI/ASI	1994 STANDARD.			
L. INTERPRET DE 2. DIMENSIONS 3. ROHS AND RE DRAWING SCALE:	RAWINGS PER A & TOLERANCES EACH COMPLIA	ASME Y14.5M- S PER ANSI/ASI	1994 STANDARD. ME B18.6.3.	DESCRIPTION:	BINDER HEAD MACHINE SCREW	
INTERPRET DE DIMENSIONS 5. ROHS AND RE DRAWING SCALE: TOLERANCES: Unless specified otherwise, all dimensions are in	RAWINGS PER / & TOLERANCES EACH COMPLIA STANDARD X.XXX + X.XX +	ASME Y14.5M- S PER ANSI/ASI NT	1994 STANDARD. ME B18.6.3. ■ MATERIAL:	DESCRIPTION:	BINDER HEAD MACHINE SCREW	
INTERPRET DE 2. DIMENSIONS 3. ROHS AND RE DRAWING SCALE: TOLERANCES: Unless specified otherwise, all dimensions are in inches	RAWINGS PER / & TOLERANCES EACH COMPLIA STANDARD X.XXX + X.XX +	ASME Y14.5M- S PER ANSI/ASI NT +/- 0.005 +/- 0.010	1994 STANDARD. ME B18.6.3. MATERIAL: NYLON FINISH:	DESCRIPTION: 1/4-20 COMBO E		
. INTERPRET DF . DIMENSIONS . ROHS AND RE DRAWING SCALE: DRAWING SCALE: Unless specified otherwise, all dimensions are in inches DRAWN BY:	RAWINGS PER A & TOLERANCES EACH COMPLIA STANDARD X.XXX + X.XX + X.X + L CLARY	ASME Y14.5M- S PER ANSI/ASI NT -/- 0.005 -/- 0.010 -/- 0.010	1994 STANDARD. ME B18.6.3. MATERIAL: NYLON FINISH: PLAIN FSCM No.	DESCRIPTION: 1/4-20 COMBO E	25CXXMCBN	
INTERPRET DE DIMENSIONS ROHS AND RE DRAWING SCALE: Unless specified otherwise, all dimensions are in nches DRAWN BY: REV:	RAWINGS PER / & TOLERANCES EACH COMPLIA STANDARD X.XXX + X.XX + X.X +	ASME Y14.5M- S PER ANSI/ASI NT +/- 0.005 +/- 0.010	1994 STANDARD. ME B18.6.3. MATERIAL: NYLON FINISH: PLAIN	DESCRIPTION: 1/4-20 COMBO E	25CXXMCBN	
INTERPRET DE DIMENSIONS S. ROHS AND RE DRAWING SCALE: TOLERANCES: Unless specified otherwise, all dimensions are in inches DRAWN BY:	RAWINGS PER / & TOLERANCES EACH COMPLIA STANDARD X.XXX + X.XX + X.XX + X.X + L CLARY APPROVAL	ASME Y14.5M- S PER ANSI/ASI NT -/- 0.005 -/- 0.010 -/- 0.010 DATE:	1994 STANDARD. ME B18.6.3. MATERIAL: NYLON FINISH: PLAIN FSCM No. 67012	DESCRIPTION: 1/4-20 COMBO E	25CXXMCBN	
2. DIMENSIONS 3. ROHS AND RE DRAWING SCALE: TOLERANCES: Unless specified otherwise, all dimensions are in inches DRAWN BY: REV:	RAWINGS PER / & TOLERANCES EACH COMPLIA STANDARD X.XXX + X.XX + X.XX + X.X + L CLARY APPROVAL	ASME Y14.5M- S PER ANSI/ASI NT -/- 0.005 -/- 0.010 -/- 0.010 DATE:	1994 STANDARD. ME B18.6.3. MATERIAL: NYLON FINISH: PLAIN FSCM No.	DESCRIPTION: 1/4-20 COMBO E PART NUMBER:	25CXXMCBN	TRONIC ONENTS