| This drawing a information co | ontained | | | | PART NUMBER | LENGTH |
|--|--|---|------|---|---------------------------|----------|
| nerein are the | | | | | 25C8MPP3P/SEX | 1/8 |
| nd proprietar | | | | | 25C12MPP3P/SEX | 3/16 |
| f Global Supp | oly LLC | | | | 25C16MPP3P/SEX | 1/4 |
| | | | | | 25C20MPP3P/SEX | 5/16 |
| | | | | | 25C24MPP3P/SEX | 3/8 |
| | | | | | 25C28MPP3P/SEX | 7/16 |
| | | | | | 25C32MPP3P/SEX | 1/2 |
| | | | 16 X | .510* | 25C40MPP3P/SEX | 5/8 |
| 492" - | | .175" - | | - Washer Diameter | 25C48MPP3P/SEX | 3/4 |
| - | ~ | | | tom | 25C56MPP3P/SEX | 7/8 |
| - | 1 | | R | And | 25C64MPP3P/SEX | 1 |
| Head | ∕—#3 Driv | | 028" | TIP | | |
| OTES: INTERPRET DF DIMENSIONS ROHS AND RE | RAWINGS PER & TOLERANCE EACH COMPLIA | ASME Y14.5M- S PER ANSI/ASI | 028" | Tip | | |
| OTES: . INTERPRET DF . DIMENSIONS . ROHS AND RE | RAWINGS PER & TOLERANCE EACH COMPLIA | ASME Y14.5M- S PER ANSI/ASI | 028" | TIP TIP | | |
| NOTES: INTERPRET DF 2. DIMENSIONS 3. ROHS AND RE DRAWING SCALE: | RAWINGS PER & TOLERANCE EACH COMPLIA | ASME Y14.5M- S PER ANSI/ASI | 028" | DESCRIPTION: | IEAD MACHINE SCREW EXTERN | IAL SEMS |
| OTES: . INTERPRET DF . DIMENSIONS . ROHS AND RE DRAWING SCALE: | RAWINGS PER & TOLERANCE EACH COMPLIA STANDARD | ASME Y14.5M- S PER ANSI/ASI | 028" | DESCRIPTION: 1/4-20 PHILLIPS PAN H PART NUMBER: | IEAD MACHINE SCREW EXTERN | IAL SEMS |
| OTES: . INTERPRET DF . DIMENSIONS . ROHS AND RE DRAWING SCALE: DRAWING SCALE: Unless specified otherwise, all dimensions are in | RAWINGS PER & TOLERANCE EACH COMPLIA STANDARD | ASME Y14.5M- S PER ANSI/ASI .NT +/- 0.005 +/- 0.010 | 028" | DESCRIPTION: 1/4-20 PHILLIPS PAN H PART NUMBER: | | IAL SEMS |
| OTES: INTERPRET DF DIMENSIONS ROHS AND RE PRAWING SCALE: OLERANCES: Inless specified therwise, all limensions are in nches | RAWINGS PER & TOLERANCE EACH COMPLIA STANDARD X.XX + X.XX + X.X + X.X + L.CLARY | ASME Y14.5M- S PER ANSI/ASI NT +/- 0.005 +/- 0.010 +/- 0.010 | 028" | DESCRIPTION: 1/4-20 PHILLIPS PAN H PART NUMBER: 25 | 5CXXMPP3P/SEX | |
| OTES: INTERPRET DF DIMENSIONS ROHS AND RE DRAWING SCALE: COLERANCES: Inless specified otherwise, all limensions are in nches DRAWN BY: REV: | RAWINGS PER & TOLERANCE EACH COMPLIA STANDARD X.XXX + X.XX + X.X + | ASME Y14.5M- S PER ANSI/ASI .NT +/- 0.005 +/- 0.010 | 028" | DESCRIPTION: 1/4-20 PHILLIPS PAN H PART NUMBER: 25 | Global Supply | LLC |
| OTES: . INTERPRET DF . DIMENSIONS . ROHS AND RE DRAWING SCALE: DRAWING SCALE: Unless specified otherwise, all dimensions are in inches DRAWN BY: | RAWINGS PER & TOLERANCE EACH COMPLIA STANDARD X.XXX + X.XX + X.XX + L.CLARY APPROVAL | ASME Y14.5M- S PER ANSI/ASI NT +/- 0.005 +/- 0.010 +/- 0.010 | 028" | DESCRIPTION: 1/4-20 PHILLIPS PAN H PART NUMBER: 25 | 5CXXMPP3P/SEX | LLC |