information co					PART NUMBER	LENGTH
herein are the					4C8MIBSP/SPA	1/8
and proprietary property					4C12MIBSP/SPA	3/16
of Global Supp	DIY LLC				4C16MIBSP/SPA	1/4
					4C20MIBSP/SPA	5/16
					4C24MIBSP/SPA	3/8
					4C32MIBSP/SPA	1/2
H	.235"	4	0.068" — X	x — –	4C40MIBSP/SPA	5/8
			1000-0000 m (100	(20)	4C48MIBSP/SPA	3/4
	$\frown$				4C56MIBSP/SPA	7/8
			/		4C64MIBSP/SPA	1
2. DIMENSIONS 3. ROHS AND RE	& TOLERANCE	S PER ANSI/ASI	#4-40 TI 1994 STANDARD ME B18.6.3	nread-		
DRAWING SCALE:			MATERIAL:	DESCRIPTION:		
STANDARD			STAINLESS STEEL	#4-40 SLOTTED BINDING HEAD MACHINE SCREW, PATCHED		
therwise, all <b>x.xx</b> +/- 0.010 timensions are in <b>x.xx</b> +/- 0.010		-/- 0.010	FINISH: PASSIVATE	PART NUMBER: 4CXXMIBSP/SPA		
		-/- 0.010				
Unless specified otherwise, all dimensions are in		-/- 0.010	FSCM No.	<b>~</b>		
Unless specified otherwise, all dimensions are in inches DRAWN BY:	L.CLARY					
Unless specified otherwise, all dimensions are in inches DRAWN BY: REV:	L.CLARY	DATE:	FSCM No. 67012			LLC
Unless specified otherwise, all dimensions are in inches DRAWN BY:	L.CLARY		67012		Jobal Supply	TRONIC
Unless specified otherwise, all dimensions are in inches DRAWN BY: REV:	L.CLARY	DATE:			Slobal Supply	TRONIC ONENTS