information co	and the ontained		Γ	PART NUMBER	LENGTH
herein are the			—	50C96HCS8	1 1/2
and proprietary property of Global Supply LLC				50C112HCS8	1 3/4
			F	50C120HCS8	1 7/8
				50C128HCS8	2
				50C144HCS8	2 1/4
				50C160HCS8	2 1/2
-0.750				50C176HCS8	2 3/4
				50C192HCS8	3
				50C208HCS8	3 1/4
			Thread Length 1.250	50C224HCS8	3 1/2
			hadadadadadadada	50C240HCS8	3 3/4
			0.500	50C256HCS8	4
2. DIMENSIONS	RAWINGS PER ASME Y14.5 & TOLERANCES PER ANSI/ EACH COMPLIANT		DESCRIPTION:		
STANDARD		GRADE 8 STEEL	1/2-13 HEX HEAD CAP SCR	1/2-13 HEX HEAD CAP SCREW	
:					
	x.xxx +/- 0.005 x.xx +/- 0.010 x.x +/- 0.010	FINISH: PLAIN	PART NUMBER: 5	OCXXHCS8	
TOLERANCES: Unless specified otherwise, all dimensions are in	x.xx +/- 0.010			OCXXHCS8	
TOLERANCES: Unless specified otherwise, all dimensions are in inches DRAWN BY: REV:	x.xx +/- 0.010 x.x +/- 0.010 LCLARY APPROVAL	PLAIN FSCM No. 67012	5		LLC
TOLERANCES: Unless specified otherwise, all dimensions are in inches DRAWN BY:	x.xx +/- 0.010 x.x +/- 0.010 LCLARY	PLAIN FSCM No. 67012	5 	obal Supply	
TOLERANCES: Unless specified otherwise, all dimensions are in inches DRAWN BY: REV:	x.xx +/- 0.010 x.x +/- 0.010 LCLARY APPROVAL	PLAIN FSCM No. 67012	5 GI GI		TRONIC ONENTS